

TRDD Application Chart

TRACTOR/ SECTION WIDTH	TRUCK TYRE SECTION WIDTH	FLAT ROUND AIRBAG	INSIDE HEAT PAD		OUTSIDE HEAT PAD	OUTSIDE AIRBAG EXTERNAL PACK WITH FLAT BAG & STRAPS	
			BIAS	RADIAL			
9.5 TO 12.4 INCHES	8.25 TO 12.00"						
260/70R TO 320/85R MM 315/80-22.5	235 TO 295 MM	TR911/13W FRB	TRR2213H	TRR2210H	TRR2213H	TRR2213E	TROC 4
SUPER SINGLE/ WIDE BASE	365/80-22.5 TO 445/65-22.5	TR1315/15W FRB	TRR2213H	TRR2210H	TRR2213H	TRR2213E	TROC 4
THE TRDD SYSTEM CAN BE EXTENDED UPWARDS TO COVER OTR TYRES UP TO 21.00 SECTION WIDTH							
OTR	13.00 TO 17.5" TYRE EXTENSION 330 TO 445 MM	TR1315/20W	MR1616H/ MR2519H*	MR3015H	TRR2621H	TRR2621E	TROC5XL
	18.00 TO 21.00" TYRE EXTENSION 455 TO 530 MM	M1721/24W	MR1616H/ MR2519H*	MR3015H	TRR2621H	TRR2621E	TROC5XL

Please note that this Application Chart is a general guide for common tyre sizes. *When selecting a Heat Pad, choose a size that will comfortably cover the largest patch that will be in used in that tyre range. This should be at least 3 or 4 inches over the patch dimensions in both orientations. Additional components available. Please enquire. If in doubt please get in touch on repair@monaflex.com